



December 2009

PRELIMINARY

# MMD90A120B

1200V 90A Rectifier Diode Module  
RoHS Compliant


## PRODUCT FEATURES

- Glass Passivated Chip
- Aluminum Oxide Ceramic Isolated Metal Baseplate
- Low Reverse Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Inductance Package



## APPLICATIONS

- Field Supply For DC Motors
- Line Rectifiers For Transistorized AC Motor Controllers
- Non-controllable Rectifiers For AC/DC Converter



## ABSOLUTE MAXIMUM RATINGS

$T_C=25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Max.	Unit
$V_{RRM}$	Repetitive Reverse Voltage		1200	V
$I_{F(AV)}$	Average Forward Current	$T_C=85^\circ\text{C}$ Rectangular, $d=0.5$	90	A
$I_{F(RMS)}$	RMS Forward Current	$T_C=85^\circ\text{C}$ Rectangular, $d=0.5$	130	A
$I_{FSM}$	Non-Repetitive Surge Forward Current	$T_J=45^\circ\text{C}$ , $t=10\text{ms}$ , 50Hz, Sine	2000	A
		$T_J=45^\circ\text{C}$ , $t=8.3\text{ms}$ , 60Hz, Sine	2200	A
$I^2t$	$I^2t$ (For Fusing)	$T_J=45^\circ\text{C}$ , $t=10\text{ms}$ , 50Hz, Sine	20000	$\text{A}^2\text{s}$
		$T_J=45^\circ\text{C}$ , $t=8.3\text{ms}$ , 60Hz, Sine	24200	$\text{A}^2\text{s}$
$P_D$	Power Dissipation		347	W
$T_J$	Junction Temperature		-40 to +150	$^\circ\text{C}$
$T_{STG}$	Storage Temperature Range		-40 to +125	$^\circ\text{C}$
$V_{isol}$	Insulation Test Voltage	AC, 50Hz, $t=1\text{min}$	3000	V
Weight			101	g

## ELECTRICAL AND THERMAL CHARACTERISTICS

$T_C=25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{RM}$	Reverse Leakage Current	$V_R=1600\text{V}$	--	--	200	$\mu\text{A}$
		$V_R=1600\text{V}$ , $T_J=125^\circ\text{C}$	--	--	5	mA
$V_F$	Forward Voltage	$I_F=200\text{A}$	--	1.33	1.5	V
		$I_F=200\text{A}$ , $T_J=125^\circ\text{C}$	--	1.3	--	V
$R_{\theta JC}$	Thermal Resistance	Junction-to-Case	--	--	0.36	$^\circ\text{C}/\text{W}$

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R. of China

Tel.: +86-519-85163708 Fax: +86-519-85162291 Post Code: 213022 Website: [www.macmicst.com](http://www.macmicst.com)

**MECHANICAL CHARACTERISTICS**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Torque	Module-to-Sink	Recommended (M6)	3		5	N · m
Torque	Module Electrodes	Recommended (M5)	2.5		5	N · m

**DA Package Outline (Dimensions in mm)**

